DALLMER

renova roof drain type 63 T FPO-PP, 460 mm, DN 125

Part number: 630889 GTIN: 4001636630889 Rebate group: 10



Description:

renova roof drain type 63 T FPO-PP, 460 mm, DN 125 conforming to DIN EN 1253 installed by pushing into the bore of pipe, usually without removing the existing roof drain, with extra wide flange for welding FPO-PP membranes directly

specification:

- multi ribbed seal

- domed grating, secured

- temporary blanking plate

material: polypropylene, UV-stabilized rubber co-moulding

Renova roof drains 63 T in special lengths 590 mm (DN 70 and DN 150) or 800 mm (DN 100 and DN 125) on request!

Flow rates tested to DIN EN 1253:

Nominal diameter	Min. flow rate accor-	Water le- vel accor-	Flow rate at water							
	ding to norm	ding to norm	level 5 mm	level 15 mm	level 25 mm	level 35 mm	level 45 mm	level 55 mm	level 65 mm	level 75 mm
DN 125	7.00 l/s	45.00 mm	0.70 l/s	2.40 l/s	4.20 l/s	6.90 l/s	9.40 l/s	12.60 l/s	16.50 l/s	20.10 l/s

Spare parts:

620866 domed grating/gravel guard type 63 T, d